

# Punches CONFIX™

for CONFIX™ bulkhead fittings, for steel, aluminium, stainless steel



These punches can be used to punch the special cutout shapes for the CONFIX™ bulkhead fittings.

For max. 2 mm stainless steel (V2A versions), sheet steel, aluminium and plastic.

The punches are suitable for the hand hydraulic punch driver and the hydraulic foot pump. For the FWS-A 50 / FWS-B 48 punches, we only recommend the hydraulic foot pump.

#### Scope of delivery:

- Punch, die, counter nut and draw stud
- robust plastic storage case

## Specifications

<b>Material</b>	Steel, hardened and burnished
<b>Flame class</b>	

## Advantages & benefits

- For the special cut-out shapes for CONFIX™
- High-quality padded transport case
- Suitable for hand hydraulic punch driver by icotek or other manufacturers

## Product types & sizes

Punch FWS-A16/20 / FWS-B11/16



Part No.	<b>80095</b>	Max. wall	<b>2 mm</b>
EAN	<b>4251269333</b>	thickness	
	<b>316</b>		
Package quantity	<b>1</b>		
Compatible with CONFIX FWS	<b>FWS-A 16, FWS-A 20, FWS B11, FWS-B 16</b>		
Number of centre punches	<b>3</b>		
Thread UNF	<b>19 mm</b>		
Punching material	<b>Plastic, Stahl (St)</b>		



Part No. **80195** Max. wall **2 mm**  
EAN **4251269333** thickness  
**354**  
Package **1**  
quantity  
Compatible **FWS-A 16,**  
with CONFiX **FWS-A 20,**  
FWS **FWS B11,**  
**FWS-B 16**  
Number of **3**  
centre  
punches  
Thread UNF **19 mm**  
Punching **Stainless**  
material **steel (V2A)**



Part No. **80096** Max. wall **2 mm**  
EAN **4251269333** thickness  
**323**  
Package **1**  
quantity  
Compatible **FWS-A 25,**  
with CONFiX **FWS-B 21**  
FWS  
Number of **3**  
centre  
punches  
Thread UNF **19 mm**  
Punching **Plastic, Stahl**  
material **(St)**

Punch FWS-A 25 / FWS-B 21 V2A



Part No. **80196** Max. wall **2 mm**  
EAN **4251269333** thickness  
**361**  
Package quantity **1**  
Compatible with CONFiX **FWS-A 25,**  
FWS **FWS-B 21**  
Number of centre punches **3**  
Thread UNF **19 mm**  
Punching material **Stainless steel (V2A)**

Punch FWS-A 32 / FWS-B 29



Part No. **80097** Max. wall **2 mm**  
EAN **4251269333** thickness  
**330**  
Package quantity **1**  
Compatible with CONFiX **FWS-A 32,**  
FWS **FWS-B 29**  
Number of centre punches **4**  
Thread UNF **19 mm**  
Punching material **Plastic, Stahl (St)**



Part No. **80197** Max. wall **2 mm**  
EAN **4251269333** thickness  
**378**  
Package quantity **1**  
Compatible with CONFiX **FWS-A 32,**  
FWS **FWS-B 29**  
Number of centre punches **4**  
Thread UNF **19 mm**  
Punching material **Stainless steel (V2A)**



Part No. **80098** Max. wall **2 mm**  
EAN **4251269333** thickness  
**347**  
Package quantity **1**  
Compatible with CONFiX **FWS-A 40,**  
FWS **FWS-B 36**  
Number of centre punches **4**  
Thread UNF **19 mm**  
Punching material **Plastic, Stahl (St)**

Punch FWS-A 40 / FWS-B 36 V2A



Part No.	<b>80198</b>	Max. wall	<b>2 mm</b>
EAN	<b>4251269333</b>	thickness	
	<b>385</b>		
Package quantity	<b>1</b>		
Compatible with CONFiX FWS	<b>FWS-A 40, FWS-B 36</b>		
Number of centre punches	<b>4</b>		
Thread UNF	<b>19 mm</b>		
Punching material	<b>Stainless steel (V2A)</b>		

Punch FWS-A 50 / FWS-B 48



Part No.	<b>80099</b>	Max. wall	<b>2 mm</b>
EAN	<b>4251269333</b>	thickness	
	<b>255</b>		
Package quantity	<b>1</b>		
Compatible with CONFiX FWS	<b>FWS-A 50, FWS-B 48</b>		
Number of centre punches	<b>4</b>		
Thread UNF	<b>19 mm</b>		
Punching material	<b>Plastic, Stahl (St)</b>		



Part No.	<b>80199</b>	Max. wall	<b>2 mm</b>
EAN	<b>4251269333</b>	thickness	
	<b>262</b>		
Package	<b>1</b>		
quantity			
Compatible	<b>FWS-A 50,</b>		
with CONFiX	<b>FWS-B 48</b>		
FWS			
Number of	<b>4</b>		
centre			
punches			
Thread UNF	<b>19 mm</b>		
Punching	<b>Stainless</b>		
material	<b>steel (V2A)</b>		