

# KEL-JUMBO | Split cable entry frames

for cables with diameters of up to 65 mm / IP54 / UL Type 12



The KEL-JUMBO cable entry system for installation of cables and conduits with a diameter of up to 65 mm, especially suited for supply cables. The innovative grommet design with the flex-membrane provides flexing and adjustment of the position for larger and more rigid cables.

We recommend round cut-outs, which can be made using standard knockout tools. Suggested cut-out: cable diameter +15 - 20%.

A flat rubber gasket is included in the shipment.



## Specifications

<b>IP rating (EN 60529)</b>	IP54
<b>UL Type (UL 50E)</b>	UL Type 12
<b>Material</b>	Polyamide
<b>Flame class</b>	UL94-V0, self-extinguishing
<b>Operating temperature</b>	-40 C° to 140 C°
<b>Properties</b>	vibration proof, UV-resistant, silicone free, anti-corrosive (V2A versions), halogen free
<b>Mounting options</b>	Screw type mounting
<b>Mounting height</b>	35 mm


## Advantages & benefits

- Installation of cables up to 65 mm in diameter
- It is possible to install rigid cables at angles
- Retrofits, repairs and maintenance can be done much more easily and quickly
- Strain relief according to EN 62444

## Product types & sizes

KEL-JUMBO 1	Part No.	42360	Height	35 mm
	EAN	4251269308550	Mounting height	35 mm
	Package quantity	1	Cut-out size	78 × 80.5 mm
	For max. no. of cables	1	No. of screw holes	4
	Max. cable diameter	65 mm	Diam. of screw holes	7 mm
	Length	110 mm	Screw material	Mild steel, galvanically zinc plated
	Width	116 mm	Suitable for grommets	1 x KTF

KEL-JUMBO 1 V2A	Part No.	42360.200	Height	35 mm
	EAN	4251269308567	Mounting height	35 mm
	Package quantity	1	Cut-out size	78 × 80.5 mm
	For max. no. of cables	1	No. of screw holes	4
	Max. cable diameter	65 mm	Diam. of screw holes	7 mm
	Length	110 mm	Screw material	Stainless steel (V2A)
	Width	116 mm	Suitable for grommets	1 x KTF


**KEL-JUMBO 2**

Part No.  
EAN  
Package quantity  
For max. no. of cables  
Max. cable diameter  
Length  
Width

**42350**  
**4251269308536**  
**1**  
**2**  
**65 mm**  
**200 mm**  
**116 mm**

Height  
Mounting height  
Cut-out size  
No. of screw holes  
Diam. of screw holes  
Screw material  
Suitable for grommets

**35 mm**  
**35 mm**  
**168 x 80.5 mm**  
**4**  
**7 mm**  
**Mild steel, galvanically zinc plated**  
**2 x KTF**

**KEL-JUMBO 2 V2A**

Part No.  
EAN  
Package quantity  
For max. no. of cables  
Max. cable diameter  
Length  
Width

**42350.200**  
**4251269308543**  
**1**  
**2**  
**65 mm**  
**200 mm**  
**116 mm**

Height  
Mounting height  
Cut-out size  
No. of screw holes  
Diam. of screw holes  
Screw material  
Suitable for grommets

**35 mm**  
**35 mm**  
**168 x 80.5 mm**  
**4**  
**7 mm**  
**Stainless steel (V2A)**  
**2 x KTF**

**icotek**<sup>®</sup>  
smart cable management